



HAYWARD®

BOBBY™ REUSABLE START-UP FILTER



Owner's Guide

Models: SP022310 and SP022320

IMPORTANT SAFETY INSTRUCTIONS

OPERATION:

The BOBBY is primarily used for start-ups, refills and renovations. It is intended to be a prefilter during the addition of water to the pool. This 5 Micron Filter reduces organics in the fill water to reduce staining of the pool surface.

The BOBBY is of a floating design that keeps the garden hose end off the pool surface to prevent the brass end from damaging the surface.

Screw the BOBBY to the end of the typical garden hose.

Place the BOBBY in the deepest portion of the pool during the filling operation.

A BOBBY should be used every time the pool is refilled. One BOBBY can be used multiple times.

- ▲ **WARNING - Read and follow all instructions in this owner's manual and on the equipment. Failure to follow instructions can cause severe injury and/or death.**
- ▲ **WARNING – Suction Entrapment Hazard.**

 Suction in suction outlets and/or suction outlet covers which are, damaged, broken, cracked, missing, or unsecured can cause severe injury and/or death due to the following entrapment hazards:

 **Hair Entrapment-** Hair can become entangled in suction outlet cover.

 **Limb Entrapment-** A limb inserted into an opening of a suction outlet sump or suction outlet cover that is damaged, broken, cracked, missing, or not securely attached can result in a mechanical bind or swelling of the limb.

 **Body Suction Entrapment-** A negative pressure applied to a large portion of the body or limbs can result in an entrapment.

 **Evisceration/ Disembowelment -** A negative pressure applied directly to the intestines through an unprotected suction outlet sump or suction outlet cover which is, damaged, broken, cracked, missing, or unsecured can result in evisceration/ disembowelment.

 **Mechanical Entrapment-** There is potential for jewelry, swimsuit, hair decorations, finger, toe or knuckle to be caught in an opening of a suction outlet cover resulting in mechanical entrapment.

- ▲ **WARNING - To Reduce the risk of Entrapment Hazards:**

- o When outlets are small enough to be blocked by a person, a minimum of two functioning suction outlets per pump must be installed. Suction outlets in the same plane (i.e. floor or wall), must be installed a minimum of three feet (3') [1 meter] apart, as measured from near point to near point.
- o Dual suction fittings shall be placed in such locations and distances to avoid "dual blockage" by a user.
- o Dual suction fittings shall not be located on seating areas or on the backrest for such seating areas.
- o The maximum system flow rate shall not exceed 6 ft/sec in the suction line.
- o Never use Pool or Spa if any suction outlet component is damaged, broken, cracked, missing, or not securely attached.
- o Replace damaged, broken, cracked, missing, or not securely attached suction outlet components immediately.
- o In addition two or more suction outlets per pump installed in accordance with latest ASME, APSP Standards and CPSC guidelines, follow all National, State, and Local codes applicable.
- o Installation of a vacuum release or vent system, which relieves entrapping suction, is recommended.

Hayward Pool Products
620 Division Street, Elizabeth, NJ 07207
Phone: (908) 355-7995
www.hayward.com