



THE ART OF OUTDOOR ILLUMINATION

The Art of Outdoor Illumination

Sollos Landscape Lighting offers a complete line of fixtures and finishes that enhance gardens, landscapes and outdoor settings. Surroundings are enriched by the subtle curves and organic feel of natural metal and architectural aluminum finishes. Dynamic fixture functionality provides safety, security and quality illumination.

Superior thermal management allows Sollos fixtures to operate both halogen and LED lamp technologies. Sollos fixtures powered by energy efficient lamps provide consistent, reliable light output.

Sollos Landscape Lighting combines aesthetic styling and ProLED power for today's landscapes.

Sollos Landscape Lighting Advantage

When powered by ProLED lamps, Sollos fixtures provide sustainable, high performance and quality LED illumination.

Powered by ProLED

ProLED lamps are constructed with LED chips, integrated drivers and transformers. ProLED lamps utilize a special heat sink to safely drive the components and achieve a long lifespan.

The input voltage range of ProLED lamps eliminate voltage drop, which is a common hurdle with traditional lamp technologies. ProLED lamps perform to specification at every input voltage within their voltage range.

For applications that normally require that the lamp is protected from the elements, Sollos offers ingress protection (IP) rated ProLED lamps.

Rigorous adherence to design and manufacturing specifications ensures consistent lamp-to-lamp color, light output and beam spreads. ProLED lamps are available in a variety of color temperatures and color-changing Red-Green-Blue-White (RGBW).

LM-79 and IES files are available for all ProLED lamps upon request.

Warranty:

Aluminum Fixtures backed by a 5 year warranty. Antique Brass, Composite, Copper, and Stainless Steel fixtures are backed by a Lifetime Limited Warranty, Commercial Transformers by a Lifetime Limited Warranty, Integrated Transformers for 2 Years and Smart Transformers 5 years. Color Changing Fixtures are backed by a 3 year warranty. For more information, please refer to the warranty statement on www.solloslighting.com.

Strongest Lamp Warranty



When installed in a Sollos fixture in recommended conditions and packaging warnings are followed, ProLED MR16 (excluding ColorSplash lamps) and non-silicon IP65-rated JC lamps are backed by a 20-year limited warranty, the strongest lamp in the industry. When installed in other fixtures, these lamps are backed by a 5-year Limited Warranty. ProLED 912 lamps, silicon IP65 rated and non-IP65-rated JC lamps are backed by a 2-year Limited Warranty. Color Changing Lamps are backed by a 3 year limited warranty. ProLED outdoor PAR36 white LED Lamps are backed by a 5 year warranty.

Think Lumens!

Efficient lighting technologies such as LED lamps produce comparable light output while consuming considerably less energy than traditional light sources. When evaluating replacement lamps, refer to lamps' light output, which is measured in lumens, rather than wattage. Lamps with relatively equivalent lumens and CBCP will provide similar illumination. So think lumens for light output and use lamp wattage to determine energy savings.

Table of Contents

4 Fixture Overview



5 Bullet, Accent & Flood Lights



6 Path Lights



7 Underwater Light, In-Ground Lights, Deck Lights, Step Lights, Ledge Lights, Pendant Light



8 Transformers

8 Accessories



9 Lamp Types

10/11 Lamp Guide

11 Color Changing Products 

Bullet, Accent & Floods

Sollos Lightings Bullet, Accent and Flood Lights are available in multiple sizes and finishes. All ground mount fixtures are packaged with a sturdy 8" ground stake and waterproof wire connectors. Sollos Lighting offers select fixtures in a kitted version which includes an LED lamp. Consult Sollos Lighting for a list of available fixture + lamp kitted items.

Fixture Styles:



Path Lights

Sollos Path Lights are available in multiple hat styles, sizes, stem lengths and finishes. Each fixture is packaged with a sturdy 8" ground stake and waterproof wire connectors. Sollos Lighting offers select Path Lights in a kitted version which includes an LED lamp. Consult Sollos Lighting for a list of available fixture + lamp kitted items.

Fixture Styles:



Hardscape, In-Ground, Hanging & Under Water Lights

Sollos Hardscape, In-Ground, Hanging and Underwater Lights are available in multiple styles, configurations and finishes. Each fixture is packaged with waterproof wire connectors. Sollos Lighting offers select fixtures in a kitted version which includes an LED lamp. Consult Sollos Lighting for a list of available fixture + lamp kitted items.

Fixture Styles:



Finishes: (see product specifications for finishes available by fixture style)



Bullet, Accent & Flood Lights

Contemporary Bullet



BCB065

Mounting Position	Up Light Only
Housing	Cast Brass or Architectural Aluminum
Lens	Clear Tempered Glass
Stem/Knuckle	Cast Brass or Architectural Aluminum
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Antique Brass	BCB065-AB
Textured Black	BCB065-TB
Textured Bronze	BCB065-TZ

Modern Bullet



BMB062

Mounting Position	Up Light Only
Housing	Architectural Aluminum
Lens	Clear Tempered Glass
Stem/Knuckle	Architectural Aluminum
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Textured Black	BMB062-TB
Textured Bronze	BMB062-TZ

Straight Bullet



BSB067

Mounting Position	Up Light Only
Housing	Cast Brass, Natural Copper or Stainless Steel
Lens	Clear Tempered Glass
Stem/Knuckle	Cast Brass
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Antique Brass	BSB067-AB
Copper	BSB067-CU
Stainless Steel	BSB067-SS

Straight Bullet



BSB062

Mounting Position	Up Light Only
Housing	Architectural Aluminum
Lens	Clear Tempered Glass
Stem/Knuckle	Architectural Aluminum
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Textured Black	BSB062-TB
Textured Bronze	BSB062-TZ

Straight Bullet



BSB060

Mounting Position	Up Light Only
Housing	Architectural Aluminum
Lens	Clear Tempered Glass
Stem/Knuckle	Architectural Aluminum
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Textured Black	BSB060-TB
Textured Bronze	BSB060-TZ

Straight Bullet



BSB054

Mounting Position	Up Light Only
Housing	Natural Copper
Lens	Clear Tempered Glass
Stem/Knuckle	Cast Brass
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR11 (35W Max) order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Copper	BSB054-CU

Contemporary Down Light Bullet



DLBCB075

Mounting Position	Up/Down
Housing	Antique Brass
Lens	Clear Tempered Glass
Stem/Knuckle	Antique Brass
Wiring	25 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	Mounting bracket included
Order Codes	
Antique Brass	DL-BCB075-AB

Straight Down Light Bullet



DLBSB077

Mounting Position	Up/Down
Housing	Antique Brass
Lens	Clear Tempered Glass
Stem/Knuckle	Antique Brass
Wiring	25 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Mounting Accessory	Mounting bracket included
Order Codes	
Antique Brass	DLBSB077-AB

PAR 36 Accent Light



BSB036

Mounting Position	Up Light Only
Housing	Cast Brass or Architectural Aluminum
Lens	None
Stem/Knuckle	Cast Brass or Architectural Aluminum
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	PAR36 G53 MP TERM order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Antique Brass	BSB036-AB
Textured Black	BSB036-TB
Textured Bronze	BSB036-TZ

Flood



FRF057

Mounting Position	Up Light Only
Housing	Cast Brass or Architectural Aluminum
Lens	Frosted Tempered Glass (includes clear lens for field install)
Stem/Knuckle	Cast Brass or Architectural Aluminum
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin order separately
Mounting Accessory	8" Ground Stake Included
Order Codes	
Antique Brass	FRF057-AB
Textured Black	FRF057-TB
Textured Bronze	FRF057-TZ



Path Lights



Modern Hat

PMH

Housing	Antique Brass
Lens	Clear Polycarbonate
Collar	Brass
Hat Diameter	7"
Stem Options	15" and 18"
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin (20W Max) order separately
Mounting Accessory	8" Ground Stake Included

Order Codes	7" Diameter	
	15" Stem	
Antique Brass		PMH070-AB-15
	18" Stem	
Antique Brass		PMH070-AB-18



Traditional Hat

PTH

Housing	Natural Copper, Antique Brass or Stainless Steel		
Lens	Clear Polycarbonate		
Collar	Brass		
Hat Diameter	4", 5.5" and 7.5"		
Stem Options	12", 15" and 18"		
Wiring	3 ft. 18-2 Lead Wire		
Voltage	12VAC		
Lamp	JC G4/GY6.35 Bi Pin (20W Max) order separately		
Mounting Accessory	8" Ground Stake Included		

Order Codes	4" Diameter	5.5" Diameter	7.5" Diameter
	12" Stem		
Antique Brass	PTH040-AB-12	PTH055-AB-12	PTH075-AB-12
Copper	PTH040-CU-12		
Stainless Steel	PTH040-SS-12		
	15" Stem		
Antique Brass	PTH040-AB-15	PTH055-AB-15	PTH075-AB-15
Copper	PTH040-CU-15		
Stainless Steel			PTH075-SS-15
	18" Stem		
Antique Brass		PTH055-AB-18	PTH075-AB-18
Copper			PTH075-CU-18
Stainless Steel			PTH075-SS-18



Dome Hat

PDO

Housing	Architectural Aluminum
Lens	Clear Polycarbonate
Collar	Architectural Aluminum
Hat Diameter	8.3"
Stem Options	12", 15" and 18"
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin (20W Max) order separately
Mounting Accessory	8" Ground Stake Included

Order Codes	8.3" Diameter	
	12" Stem	
Textured Black		PDO083-TB-12
Textured Bronze		PDO083-TZ-12
	15" Stem	
Textured Black		PDO083-TB-15
Textured Bronze		PDO083-TZ-15
	18" Stem	
Textured Black		PDO083-TB-18
Textured Bronze		PDO083-TZ-18



Mushroom Hat

PMU

Housing	Architectural Aluminum
Lens	Clear Polycarbonate
Hat Diameter	5"
Stem Options	15"
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin (20W Max) order separately
Mounting Accessory	8" Ground Stake Included

Order Codes	5" Diameter	
	15" Stem	
Textured Black		PMU050-TB-15
Textured Bronze		PMU050-TZ-15



Straight Hat

PSH

Housing	Architectural Aluminum
Lens	Clear Polycarbonate
Collar	Architectural Aluminum
Stem Options	12", 15" and 18"
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi PIN (20W Max) order separately
Mounting Accessory	8" Ground Stake Included

Order Codes	4" Diameter	5.5" Diameter	7.5" Diameter	9" Diameter
	12" Stem			
Textured Black	PSH040-TB-12	PSH055-TB-12	PSH075-TB-12	
Textured Bronze	PSH040-TZ-12	PSH055-TZ-12	PSH075-TZ-12	
	15" Stem			
Textured Black	PSH040-TB-15	PSH055-TB-15	PSH075-TB-15	PSH090-TB-15
Textured Bronze	PSH040-TZ-15	PSH055-TZ-15	PSH075-TZ-15	PSH090-TZ-15
	18" Stem			
Textured Black		PSH055-TB-18	PSH075-TB-18	PSH090-TB-18
Textured Bronze		PSH055-TZ-18	PSH075-TZ-18	PSH090-TZ-18

Underwater Light



UWL-R33-AB	
Housing	Cast brass body and cap with large black thumb screws
Lens	High impact clear tempered flat glass
Cover	Brass
Rating	IP68
Aiming	Surface mount aiming bracket
Wiring	25 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (LED 4.5W MAX) order separately
Order Codes	
Antique Brass	UWL-R33-AB

Rock Guard



IGG049	
Housing	Single-Piece Compression Molded Polyester Composite
Lens	Shock and Heat-Resistant Clear Tempered Glass
Cover	Brass, Composite or Stainless Steel
Installation	Sand, Gravel, not for use in concrete
Aiming	Adjustable Lamp Bracket Provides +/- 15° of Tilt
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Order Codes	
Antique Brass	IGG049-AB
Composite Black	IGG049-CB
Stainless Steel	IGG049-SS

In-Ground Lights

Trim Ring



IGT049	
Housing	Single-Piece Compression Molded Polyester Composite
Lens	Shock and Heat-Resistant Clear Tempered Glass
Cover	Brass, Composite or Stainless Steel
Installation	Sand, Gravel, not for use in concrete
Aiming	Adjustable Lamp Bracket Provides +/- 15° of Tilt
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (50W Max) order separately
Order Codes	
Antique Brass	IGT049-AB
Composite Black	IGT049-CB
Stainless Steel	IGT049-SS

Well Light



WPO055	
Housing	Composite Black ABS
Lamp Holder	Adjustable Height and Angle
Installation	Sand, Gravel, not for use in concrete
Aiming	360° Lamp Rotation
Wiring	3 ft. 18-2 Lead Wire with Slip-on Connectors
Voltage	12VAC
Lamp	PAR36 (50W Max) order separately
Order Codes	
Well Light	WPO055-CB

Deck Lights

Post Light



DPL033	
Housing	Die Cast Aluminum or Brass
Lens	Shock and Heat-Resistant Frosted Tempered Glass
Mounting	Surface Mounting Plate
Wiring	6 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin (10W Max) order separately
Order Codes	
Antique Brass	DPL033-AB
Textured Black	DPL033-TB
Textured Bronze	DPL033-TZ

Under-Step Light



DUS060	
Housing	Die Cast Aluminum
Cover	Antique Brass, Natural Copper or Stainless Steel
Lens	Shock and Heat-Resistant Frosted Tempered Glass
Mounting	Optional Stainless Steel Mounting Plate for Hardscape Installations order separately
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	912 Wedge (20W Max) order separately
Length	6"
Order Codes	
Antique Brass	DUS060-AB
Copper	DUS060-CU
Stainless Steel	DUS060-SS
Optional Mounting Plate	MP06

Louver Faceplate



SBL048	
Housing	Die Cast Aluminum with Adjustable Mounting Brackets
Faceplate	Architectural Grade Aluminum
Faceplate Dimension	4.85" x 2.96"
Faceplate Mounting	Adjustable Nylon Mounts Correct Undesired Tilt
Lens	Shock and Heat-Resistant Frosted Tempered Glass
Aiming	Adjustable Socket for Proper Lamp Centering
Wiring	6 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin (10W Max) order separately
Order Codes	
Textured Black	SBL048-TB
Textured Bronze	SBL048-TZ

Trim Faceplate



SBT048	
Housing	Die Cast Aluminum with Adjustable Mounting Brackets
Faceplate	Copper, Stainless Steel, or Architectural Grade Aluminum
Faceplate Dimension	4.85" x 2.96"
Faceplate Mounting	Adjustable Nylon Mounts Correct Undesired Tilt
Lens	Shock and Heat-Resistant Frosted Tempered Glass
Aiming	Adjustable Socket for Proper Lamp Centering
Wiring	6 ft. 18/2 Lead Wire
Voltage	12VAC
Lamp	JC G4/GY6.35 Bi Pin (10W Max) order separately
Order Codes	
Copper	SBT048-CU
Natural Brass	SBT048-BR
Textured Black	SBT048-TB
Textured Bronze	SBT048-TZ

Ledge Lights



LLA055	
Housing	Architectural Aluminum or Brass
Lens	Shock and Heat-Resistant Frosted Tempered Glass
Wiring	10 ft. 18-2 lead-wire
Voltage	12VAC
LED	0.6 Watt, 2700K LED / 2 Watt, RGBW LED
Order Codes	
Antique Brass	LLA055/827/AB
Textured Black	LLA055/827/TB
Smooth Bronze	LLA055/827/TZ
Replacement Light Module	LLA055/827

Pendant Light



HLS043	
Housing	Antique Brass
Lens	Clear Tempered Glass
Base	Antique Brass
Wiring	3 ft. 18-2 Lead Wire
Voltage	12VAC
Lamp	MR16 (35W Max) order separately
Mounting Accessory	Stainless Steel Hanger Cable Included
Order Codes	
Antique Brass	HLS043-AB

Transformers

Commercial



TR15SS-600

TR15SS-300

Max VA	Voltage Taps	Order Codes
150VA	12/13/14/15 VAC	TR15SS-150
300VA	12/13/14/15 VAC	TR15SS-300
600VA	12/13/14/15 VAC	TR15SS-600

Integrated



TR12PC-INT-100

TR12SS-INT-120
TR12SS-INT-200

TR15SS-INT-300

Max VA	Voltage Taps	Order Codes
100VA	12VAC	TR12PC-INT-100
120VA	12VAC	TR12SS-INT-120
200VA	12VAC	TR12SS-INT-200
300VA	12/13/14/15 VAC	TR15SS-INT-300

OPERATION:

A = Auto On/Off "Dusk-to-Dawn"

O = Manual On

(120W, 200W & 300W) 1 Through 9 = On at

Dusk/Off at 1 to 9 hours

(100W) 4, 6 or 8 = On at Dusk/Off at 4, 6 or

8 hours

Smart (Bluetooth controlled)



TR14ST-150

Max VA	Voltage Taps	Order Codes
150VA	14VAC (x2)	TR14ST-150

OPERATION:

Bluetooth Phone App controlled

Astronomical timer

Pre-loaded Programs

FREE SOLLOS® ECLIPSE app available from the app store for Apple® or Google Play Store™ for Android™



Accessories

Commercial Transformers



TMA
Analog Timer

24-hour clock
3 on/off settings per day



TMDA
Digital Astronomic Timer

Build-in daylight saving time function
Auto adjusts to sunrise/sunset for dusk/dawn settings



PCS
Photocell
6" Lead

Fixtures



DMT SERIES
Deck Mount

Order Codes	2.7"
Antique Brass	DMT027-AB
Textured Black	DMT027-TB
Textured Bronze	DMT027-TZ

For surface mounting fixtures



RSR SERIES
Fixture Risers

Order Codes	12" Length	18" Length
Antique Brass	RSR12-AB	RSR18-AB
Textured Black	RSR12-TB	RSR18-TB
Textured Bronze	RSR12-TZ	RSR18-TZ

For increasing the mounting height of fixtures



GS08
Ground Stake
8" ABS



SCSBTR
Blue Tooth Repeater
Increases the signal strength range on the Sollos ColorSplash RGBW color changing lamps and fixtures.



SEC-182-25
Extension Cable
25' 18/2 cable
Outdoor heat shrink splice connectors


LED Lamp Types



JC10 912 Wedge



JC10 BA15s



JC10 G4



JC10 RGBW G4



JC20 G4



JC20 BA15s



JC35 GY6.35



JC50 GY6 35



JC3 G4 3.3W



JC3 G4 2.5W



JC1 G4



JC2S G4



JC2 G4 1.6W



JC2 G4 2.3W



JC20 BA15s



JC20 912 Wedge



JC20 3155 Wedge



MR16



MR11



G25



ST19



B11



A19



S14



T10



PAR36

Lamp Guide

Watt	Base	Product #	Product Code	Description	Beam Spread	Dimmable	Volts	Color Temp.	CRI	Lumens	Useful Life*	Wattage Equivalent
Traditional JC Series												
JC10												
1W	912 Wedge	80791	912/1WW/LED2	Omnidirectional			10-18	3000K	82	75	20,000	10
1.5 Watt	BA15s	80692	JC10/1WW/BA15S/LED	Omnidirectional			10-24	3000K	82	150	30,000	10
1.5 Watt	G4	80693	JC10/1WW/LED	Omnidirectional			10-24	3000K	82	150	30,000	10
1.5 Watt	G4	82143	JC10/RGBW/LED	IP20, Top Lit	100°	Yes	10-15	RGB 2700K	80	120	40,000	10
JC20												
2.4 Watt	BA15s	80691	JC20/2WW/BA15S/LED	Omnidirectional			10-24	3000K	82	250	30,000	20
2.4 Watt	G4	80690	JC20/2WW/LED	Omnidirectional			10-24	3000K	82	250	30,000	20
2.4 Watt	G4	80815	JC20/2NW/LED	Omnidirectional			10-24	5000K	82	260	30,000	20
JC35												
4.5 Watt	GY6.35	80830	JC35/4WW/LED	Omnidirectional			10-18	3000K	82	450	30,000	35
JC50												
5.5 Watt	GY6.35	81997	JC50/5WW/LED	Omnidirectional			10-18	3000K	82	550	30,000	50
JC3												
3.3 Watt	G4	81078	JC3VWFL/827/LED	100° Very Wide Flood			12	2700K	82	200	25,000	20
IP Rated JC Series												
JC3												
2 Watt	G4	81996	JC3/830/OMNI/IP65/LED	Omnidirectional, IP65 Rated, Silicon			10-15	3000K	80	300	15,000	20
JC1												
1.2 Watt	G4	81998	JC1/830/OMNI/IP65/LED	Omnidirectional, IP65 Rated, Silicon			10-15	3000K	82	110	15,000	10
JC2S												
1.4 Watt	G4	81091	JC2S/827/LED2	IP65 Rated			10-15	2700K	82	140	40,000	20
1.4 Watt	G4	81092	JC2S/830/LED2	IP65 Rated			10-15	3000K	82	150	40,000	20
JC2												
1.5 Watt	G4	81999	JC2/830/OMNI/IP65/LED	Omnidirectional, IP65 Rated, Silicon			10-15	3000K	82	200	15,000	20
2.3 Watt	G4	81109	JC2/827/LED2	Omnidirectional, IP65 Rated			10-15	2700K	82	250	40,000	20
2.3 Watt	G4	81108	JC20/2WW/LED2	Omnidirectional, IP65 Rated			10-15	3000K	82	250	40,000	20
JC20												
2.3 Watt	BA15s	81100	JC20/2WW/BA15S/LED2	IP65 Rated			10-15	3000K	82	250	40,000	20
1.2 Watt	Wedge	81102	912/1WW/LED2	IP65 Rated			10-15	3000K	82	120	40,000	10
2.3 Watt	Wedge	81101	3155/2WW/LED2	IP65 Rated			10-15	3000K	82	250	40,000	20
MR16												
2.5 Watt	GU5.3	81055	MR16NFL10/827/LED	Narrow Flood	20°	Yes	10-18	2700K	82	200	40,000	10
2.5 Watt	GU5.3	81079	MR16NFL10/830/LED	Narrow Flood	20°	Yes	10-18	3000K	82	210	40,000	10
2.5 Watt	GU5.3	81056	MR16FL10/827/LED	Flood	40°	Yes	10-18	2700K	82	200	40,000	10
2.5 Watt	GU5.3	81077	MR16FL10/830/LED	Flood	40°	Yes	10-18	3000K	82	210	40,000	10
2.5 Watt	GU5.3	81058	MR16FL10/850/LED	Flood	40°	Yes	10-18	5000K	82	230	40,000	10
2.5 Watt	GU5.3	81057	MR16WFL10/827/LED	Wide Flood	60°	Yes	10-18	2700K	82	200	40,000	10
2.5 Watt	GU5.3	81080	MR16WFL10/830/LED	Wide Flood	60°	Yes	10-18	3000K	82	210	40,000	10
4 Watt	GU5.3	81059	MR16BBF/827/LED	Narrow Flood	20°	Yes	10-18	2700K	82	300	40,000	20
4 Watt	GU5.3	81081	MR16BBF/830/LED	Narrow Flood	20°	Yes	10-18	3000K	82	310	40,000	20
4 Watt	GU5.3	81060	MR16BAB/827/LED	Flood	40°	Yes	10-18	2700K	82	300	40,000	20
4 Watt	GU5.3	81062	MR16BAB/830/LED	Flood	40°	Yes	10-18	3000K	82	310	40,000	20
4 Watt	GU5.3	81063	MR16BAB/850/LED	Flood	40°	Yes	10-18	5000K	82	340	40,000	20
4 Watt	GU5.3	81061	MR16WFL20/827/LED	Wide Flood	60°	Yes	10-18	2700K	82	300	40,000	20
4 Watt	GU5.3	81082	MR16WFL20/830/LED	Wide Flood	60°	Yes	10-18	3000K	82	310	40,000	20
4.5 Watt	GU5.3	81064	MR16FRA/827/LED	Narrow Flood	20°	Yes	10-15	2700K	82	380	40,000	35
4.5 Watt	GU5.3	81083	MR16FRA/830/LED	Narrow Flood	20°	Yes	10-15	3000K	82	390	40,000	35
4.5 Watt	GU5.3	81065	MR16FMW/827/LED	Flood	40°	Yes	10-15	2700K	82	380	40,000	35
4.5 Watt	GU5.3	81067	MR16FMW/830/LED	Flood	40°	Yes	10-15	3000K	82	390	40,000	35
4.5 Watt	GU5.3	81068	MR16FMW/850/LED	Flood	40°	Yes	10-15	5000K	82	430	40,000	35
4.5 Watt	GU5.3	81066	MR16WFL35/827/LED	Wide Flood	60°	Yes	10-15	2700K	82	380	40,000	35
4.5 Watt	GU5.3	81084	MR16WFL35/830/LED	Wide Flood	60°	Yes	10-15	3000K	82	390	40,000	35
8 Watt	GU5.3	81069	MR16EXZ/827/LED	Narrow Flood	20°	Yes	10-18	2700K	82	590	40,000	50
8 Watt	GU5.3	81085	MR16EXZ/830/LED	Narrow Flood	20°	Yes	10-18	3000K	82	600	40,000	50
8 Watt	GU5.3	81070	MR16EXN/827/LED	Flood	40°	Yes	10-18	2700K	82	590	40,000	50
8 Watt	GU5.3	81072	MR16EXN/830/LED	Flood	40°	Yes	10-18	3000K	82	600	40,000	50
8 Watt	GU5.3	81073	MR16EXN/850/LED	Flood	40°	Yes	10-18	5000K	82	660	40,000	50
8 Watt	GU5.3	81071	MR16FNV/827/LED	Wide Flood	60°	Yes	10-18	2700K	82	590	40,000	50
8 Watt	GU5.3	81086	MR16FNV/830/LED	Wide Flood	60°	Yes	10-18	3000K	82	600	40,000	50

May not be compatible with all dimming systems. Use on incompatible systems may shorten lamp life. Lamps should be tested in the application for compatibility prior to full installations on circuits using such devices. Acceptable for use in sealed metal landscape fixtures when protected from the elements.

Lamp Guide

Watt	Base	Product #	Product Code	Description	Beam Spread	Dimmable	Volts	Color Temp.	CRI	Lumens	Useful Life	Wattage Equivalent
MR16 - Black Body & RGBW												
4 Watt	GU5.3	81103	MR16NFL4/827/LED	Narrow Flood	20°	Yes	10-15	2700K	82	250	30,000	20
4 Watt	GU5.3	81098	MR16FL4/827/LED	Flood	40°	Yes	10-15	2700K	82	250	30,000	20
4 Watt	GU5.3	81099	MR16WFL4/827/LED	Wide Flood	60°	Yes	10-15	2700K	82	250	30,000	20
4.5 Watt	GU5.3	82094	MR16NFL4.5/827/LED	Narrow Flood	20°	Yes	10-15	2700K	82	390	30,000	35
4.5 Watt	GU5.3	82095	MR16FL4.5/827/LED	Flood	40°	Yes	10-15	2700K	82	390	30,000	35
6 Watt	GU5.3	82099	MR16FL6/RGB-W/LED	Flood	40°	Yes	10-15	RGB-2700K	80	400	40,000	35
MR11												
3 Watt	GU4	81093	MR11FTD/827/LED	Flood	30°	Yes	10-18	2700K	82	230	40,000	20
3 Watt	BA15d	81094	MR11FTD/827/BA15D/LED	Flood	30°	Yes	10-15	2700K	82	230	40,000	20
3 Watt	GU4	81095	MR11FTD/850/LED	Flood	30°	Yes	10-18	5000K	82	250	40,000	20
3 Watt	GU4	81096	MR11FTDC/827/LED	Narrow Flood	22°	Yes	10-18	2700K	82	230	40,000	20
G25												
5.5 Watt	E26	85047	G25CL5ANT/827/LED2	Clear Filament		Yes	120	2700K	82	500	15,000	60
ST19												
5.5 Watt	E26	85044	ST19AMB5ANT/822/LED	Amber Filament		Yes	120	2200K	82	400	15,000	40
T10												
4.5 Watt	E26	85075	T10AMB4ANT/822/LED2	Amber Filament		Yes	120	2200K	82	300	15,000	40
B11												
4.5 Watt	E26	85055	B11CL4ANT/827/E26/LED2	Clear Filament		Yes	120	2700K	82	220	15,000	40
A19												
5 Watt	E26	85037	A19CL5ANT/827/LED2	Clear Filament		Yes	120	2700K	82	450	15,000	40
5 Watt	E26	85038	A19AMB5ANT/820/LED2	Amber Filament		Yes	120	2000K	82	340	15,000	40
S14												
2 Watt	E26	81139	S14CL2ANT/827/LED	Clear Filament		No	120	2700K	82	200	15,000	25
2 Watt	E26	81140	S14AMB2ANT/822/LED	Amber Filament		No	120	2200K	82	160	15,000	25
2 Watt	E26	82139	S14CL2ANT/827/LED2	Clear Filament		Yes	120	2700K	82	200	15,000	25
PAR36												
4.5 Watt	MP Term	81074	PAR36WFL4/827/IP67/LED	Outdoor IP67	32°	Yes	10-15	2700K	82	300	40,000	20
6.5 Watt	MP Term	81075	PAR36WFL6/827/IP67/LED	Outdoor IP67	32°	Yes	10-15	2700K	82	450	40,000	35
12.5 Watt	MP Term	81076	PAR36WFL12/827/IP67/LED	Outdoor IP67	32°	Yes	10-15	2700K	82	800	40,000	50
10 Watt	MP Term	82142	PAR36WFL10/RGBW/IP68/LED	Outdoor IP68	40°	Yes	10-15	RGB-2700K	80	800	40,000	50

May not be compatible with all dimming systems. Use on incompatible systems may shorten lamp life. Lamps should be tested in the application for compatibility prior to full installations on circuits using such devices. Acceptable for use in sealed metal landscape fixtures when protected from the elements.

ColorSplash® Color Changing Products

Our color-changing LED lights set the stage for dazzling outdoor spaces. Jazz up your landscaping with the perfect hue to fit your mood. Change the settings quickly and easily from your phone with our free Sollos® ColorSplash® Blue Tooth APP.

- RGB-W color-changing plus white in single product
- Blue Tooth controlled with the Sollos® ColorSplash® app
- Maximum app connection of 128 devices
- 80% more efficient than halogen equivalent
- Three year limited warranty

MR16 RGB-W LED Lamp

- 80 or above CRI (Color Rendering Index)
- 40° Beam
- RGB and Warm White (2700K)



Watt	Base	Product #	Product Code
6W	GU5.3	82099	MR16FL6/RGBW/LED

See Lamp Guide for additional specifications

JC10 RGB-W LED Lamp

- Compact size
- Designed for use in Sollos path lights



Watt	Base	Product #	Product Code
1.5W	G4	82143	JC10/RGBW/LED

See Lamp Guide for additional specifications

PAR36 RGB-W LED Lamp

- IP68 rated for waterproof installations
- Multi-purpose base for slip-on or screw terminal connections
- 40° Beam spread



Watt	Base	Product #	Product Code
10W	MP Term	82142	PAR36WFL10/RGBW/IP68/LED

See Lamp Guide for additional specifications

Ledge Light RGB-W LED Fixture

- IP65 rated for outdoor installations
- 10' cable length



Watt	Material	Product #	Product Code
2W	Textured Black Aluminum	27516	LLA055/RGBW/2/TB
2W	Textured Bronze Aluminum	27517	LLA055/RGBW/2/TZ
2W	Replacement LED Module	27518	LLA055/RGBW

See page #7 for additional specifications

Bluetooth Repeater

To help ensure a seamless installation while increasing coverage and range, Sollos® Lighting highly recommends using our Blue Tooth Repeater on your ColorSplash® Landscape Lighting installation. Typical installations generally require just one repeater for the entire ColorSplash® Landscape Lighting installation while larger installations may require additional repeaters. Please see the Sollos® ColorSplash® Blue Tooth Repeater installation guide for more information.



Product #	Product Code
27514	SCSBTR

See Lamp Guide for additional specifications

FREE Sollos® ColorSplash® app

Download the FREE Sollos® ColorSplash® app and bring the power of color changing lighting control to your fingertips! Using the app, you can connect lighting, create zones, turn on/off, change or create programs...and so much more!





Sollos Landscape Lighting

1415 Vantage Park Drive, Suite 400

Charlotte, NC 28203

Toll Free 888-976-5567

www.solloslighting.com